

Automatic Transmission Fluid OE GOLD

With ACDelco GM OE DEXRON®-VI, DEXRON® ULV and ACDelco Gold ATF III, you'll be able to keep your customer's transmissions working at their best.

PRODUCT FEATURES:

- Synthetic fluid with high shear stability and oxidation resistance
- Provides superior year-round protection and performance
- Provides anti-wear protection to extend equipment life
- Helps smoother shifting and reduced shudder
- Helps to extend service life and performance

ATF Type	Available Qty(s)	Applications
DEXRON®VI†	Quart, Gallon, Drum or BIB (6 gallons)	GM automatic transmissions where a DEXRON®VI, earlier-generation DEXRON® or AW-1 fluid is specified Ford automatic transmissions/transaxles where a MERCON® fluid is specified
DEXRON®ULV	Quart	Full synthetic ultra-low viscosity for use in 8, 9 and 10 speed transmissions Not a suitable replacement for DEXRON® III or DEXRON® VI
ATF Type	Quantities	Applications
ATF Type III (H)*	Quart, Gallon, Drum, BIB(6 gallons)	GM automatic transmissions in 2005 and earlier model-year vehicles that are no longer under warranty, where the OEM previously specified DEXRON®-III H, DEXRON®-II or DEXRON® ATF



GM OE DEXRON®VI



GM OE DEXRON®ULV



ATF TYPE III (H)

†Recommended for use in GM transmissions model year 2006 and newer calling for DEXRON®-VI and replaces DEXRON III (H) and DEXRON II (E). Also recommended for any other vehicle manufacturers that call for DEXRON®-VI, Type III or II (E).

*Not recommended for use in newer automatic transmissions that require a GM DEXRON-VI, Ford MERCONLV, FordMERCON SP or Ford MERCON V fluid for warranty coverage. Not recommended for continuously variable transmission (CVTs).

These automatic transmission fluids are not for use in continuously variable or dual-clutch transmissions, which require specialized fluids. Consult the Owner's Manual for the correct fluid recommendation. Misapplication may cause severe performance problems.

Always refer to the Owner's Manual for proper ATF recommendations.